

CERTIFICATE OF COMPLIANCE

Certificate Number R40822
Report Reference R40822-20220607
Issue Date 2022-JUNE-07

Issued to: SHANGHAI YOULAN ENVIRONMENTAL TECHNOLOGY CO., LTD.
58 FUMIN BRANCH ROAD
HENGSHA TOWN
CHONGMING DISTRICT SHANGHAI , SHANGHAI,
200040 CHINA

**This certificate confirms that
representative samples of**

FILTER UNITS, AIR
See Addendum Page for Models

Have been evaluated by UL in accordance with the
Standard(s) indicated on this Certificate.

Standard(s) for Safety:
Additional Information:

Standard for Air Filter Units - UL 900
See UL Product iQ® at <https://iq.ulprospector.com> for
additional information.

This Certificate of Compliance indicates that representative samples of the product described in the certification report have met the requirements for UL certification. It does not provide authorization to apply the UL Mark. Only the Authorization Page that references the Follow-Up Services Procedure for ongoing surveillance provides authorization to apply the UL Mark.

Only those products bearing the UL Mark should be considered as being UL Certified and covered under UL's Follow-Up Services.

Look for the UL Certification Mark on the product.



Bruce Mahrenholz, Conformity Assessment Director
UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Customer Service at <http://ul.com/aboutul/locations/>



CERTIFICATE OF COMPLIANCE

Certificate Number R40822
Report Reference R40822-20220607
Issue Date 2022-JUNE-07

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements.

| Products Covered | Product Designation | Nomenclature |
|--|------------------------------------|--------------|
| Dry-type, throw-away air filter units, max. 98 mm, 3-7/8 in. depth | Ultrair | |
| Dry-type, throw away, air filter units, max. 117 mm (4.6 in) depth | Ultrair PTFE | |
| Dry-type, throw away, extended area air filter units, maximum depth of 560 mm (22 in) and maximum 8 pockets, | Unipak (Chemical Fiber Filter Bag) | |
| Dry-type, throw away, extended area air filter units, maximum depth of 560 mm (22 in) and maximum 8 pockets, | Unipak (Glass Fiber Filter Bag) | |
| Dry-type, throw-away air filter units, max. 292 mm (11-1/2 in) depth | Ultrair MV | |
| Dry-type, throw-away air filter units, max. 292 mm (11-1/2 in) depth | Uniair H | |
| Dry-type, throw-away air filter units, max. 292 mm (11-1/2 in) depth | Uniair HC | |
| Dry-type, throw-away air filter units, max. 292 mm (11-1/2 in) depth | Uniair M | |
| Dry-type, throw-away air filter units, max. 51 mm (2 in) depth | Upleat | |
| Dry-type, throw-away air filter units, max. 51 mm (2 in) depth | Uwash | |
| Dry-type, replaceable medium air filter media, max. 305 mm, 12 in. depth | Unicarb 1 | |
| Dry-type, replaceable medium air filter media, max. 305 mm, 12 in. depth | Unicarb 2 | |
| Dry-type, replaceable medium air filter media, max. 305 mm, 12 in. depth | Unicarb 4 | |
| Dry-type, replaceable medium air filter units, max. 305 mm, 12 in. depth | Unipure HG | |
| Dry-type, replaceable medium air filter units, max. 305 mm, 12 in. depth | Unipure IG | |
| Dry-type, replaceable medium air filter units, max. 305 mm, 12 in. depth | Unipure MG | |
| Dry-type, replaceable medium air filter media, max. 305 mm, 12 in. depth | Unisorb A1 | |

B. Mahlenz

Bruce Mahlenz, Conformity Assessment Director

UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Customer Service at <http://ul.com/about/locations/>



CERTIFICATE OF COMPLIANCE

Certificate Number R40822
Report Reference R40822-20220607
Issue Date 2022-JUNE-07

| Products Covered | Product Designation | Nomenclature |
|--|---------------------|--------------|
| Dry-type, replaceable medium air filter media, max. 305 mm, 12 in. depth | Unisorb B1 | |
| Dry-type, replaceable medium air filter media, max. 305 mm, 12 in. depth | Unisorb B2 | |
| Dry-type, replaceable medium air filter media, max. 305 mm, 12 in. depth | Unisorb T1 | |



Bruce Mahrenholz, Conformity Assessment Director
UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Customer Service at <http://ul.com/aboutul/locations/>

